


Spreading Joy Enhancing Lives



Key Features

- Available Sizes
 - 20 mm to 400 mm O.D.

- · Light weight.
- Maintenance Free Resistant to any type of corrosion.
- Safe for conveying potable water.
- High chemical resistance.
- · Smooth bore.
- · Economical.

Working Pressure

Working Pressure 2.5kg/cm² to 10kg/cm²

Applications

Irrigation in agriculture, potable water supply, conveying of water under pressure.

Product Specifications

IS 4985 : 2000 (Extract)		Wall Thickness for working pressure classes (mm)									
Outside Diameter (mm)	Tolerance on Outside Diameter (mm)	Class 1 2.5 kg/cm²		Class 2 4 kg/cm²		Class 3 6 kg/cm²		Class 5 10 kg/cm²		Plumbing Pipes	
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
20	+0.3	_	_	_	_	_	_	1.1	1.5	2.8	3.3
25	+0.3	_	_	_	_	_	_	1.4	1.8	2.9	3.4
32	+0.3	_	_	_	_	_	_	1.8	2.2	3.4	3.9
40	+0.3	_	_	_	_	1.4	1.8	2.2	2.7	3.6	4.2
50	+0.3	_	_	_	_	1.7	2.1	2.8	3.3	3.7	4.3
63	+0.3	_	_	1.5	1.9	2.2	2.7	3.5	4.1	_	_
75	+0.3	_	_	1.8	2.2	2.6	3.1	4.2	4.9	_	_
90	+0.3	1.3	1.7	2.1	2.6	3.1	3.7	5.0	5.7	_	_
110	+0.4	1.6	2.0	2.5	3.0	3.7	4.3	6.1	7.0	_	_
125	+0.5	1.8	2.2	2.9	3.4	4.3	6.0	6.9	8.0	_	_
140	+0.5	2.0	2.4	3.2	3.8	4.8	5.5	7.7	8.7	_	_
160	+0.5	2.3	2.8	3.7	4.3	5.4	6.2	8.8	9.9	_	_
180	+0.6	2.6	3.1	4.2	4.9	6.1	7.0	9.9	11.1	_	_
200	+0.6	2.9	3.4	4.6	5.3	6.8	7.7	11.0	12.3	_	_
225	+0.7	3.3	3.9	5.2	6.0	7.6	8.6	12.4	13.9	_	_
250	+0.8	3.6	4.2	5.7	6.5	8.5	9.6	13.8	15.4	_	_
280	+0.9	4.1	4.8	6.4	7.3	9.5	10.7	15.4	17.2	_	_
315	+1.0	4.6	5.3	7.2	8.2	10.7	12.0	17.3	19.3	_	_
355	+1.1	5.1	5.9	8.1	9.4	12.0	13.8	19.6	22.6	_	_
400	+1.2	5.8	6.7	9.1	10.5	13.5	15.6	22.0	25.3	_	

(DUTRON)®

DUTRON POLYMERS LIMITED

"Dutron House", Nr. Mithakhali Underbridge Navrangpura, Ahmedabad 380 009 Gujarat, India.

Tel: +91 79 2656 1849, 2642 7522

Fax: +91 79 2642 0894 Email: sales@dutronindia.com Website: www.dutronindia.com Authorised Dealer